

Industrial vacuum cleaners for dust

Electric

UT 1,1 / 1,3 / 2,2 kW EB

Built-in or under a desk for use in
Industry and Trade

Range of applications

The side channel blower is designed for continuous use, even in multi-shift operation, are suitable. A microfiber bag filter as a prefilter to minimize the dust load of the PTFE-coated main filter. Optional filters available with certified H14.

Different voltages are available on request. Equipment has to be agreed individually.

Properties/Advantages

- Continuous Fixed side channel blowers
- Tank bottom plate to be rotated and easily fixable
- Stainless steel tank
- Very easy emptying
- Simple operation and maintenance
- Space-saving design

The suction cups are offered as standard in three performance classes 1.1 / 1.3 / 2.2 kW. Individually, the suction volume can be adjusted exactly to the customer.

The extremely simple operation and cleaning capabilities of the vacuum cleaner designed specifically for industrial applications. The modular system of the vacuum can at any time eg be retrofitted with H14 filter.

The Standard Model UT EB sucks the suction material through the input connection on the dirt container closable in a filter bag. This system protects the downstream filter elements and reduced to a multiple of the cost of emptying the container. The paper bag / microfiber pouch also serve to protect the user against contact with product residues. As transport equipment (for example, granules, etc.) to create vacuum filtration and the residual dust, continuous extraction of dust from manufacturing or packaging equipment and used as soft water heater.



Accessories	
Description	Art.Nr.
Filter bag	see catalogue
Suction hose	see catalogue
Suction accessories	see catalogue
H - Filter	see catalogue

Technical data	
Engine	electric motor
Power	1,1 / 1,3 / 2,2 kW
Power consumption	400 V / 50 Hz. [IP 65]
Intake volume max.	145 / 210 / 320 m³/h
Vacuum max.	170 / 170 / 180 mbar
Container volume	10 / 15 / 20 / 35 / 45 Liter
Total filter area	5.000 cm² / (H:20.000 mm²)
Connection hose	50 mm, reduceable
Weight	optional
Noise level	69 - 74 dB (A)
Dimensions L x W x H	optional

Feature

Revolving container

