

Industrial vacuum cleaner for flammable dust

Air driven

DGS ** EX

CE 0158 EX II 1/2 GD II B T6 RL 94/9/EG



Mobile vacuum cleaner for Ex-Zone 1/2 and 21/22

Application

This vacuum cleaner is tested and certificated for applications where all kind of none flammable and flammable dust is to be recovered. Mobile, powerfull vacuum cleaner, which also can be used as a stationary vacuum unit in the chemical-, pharmaceutical- and petrochemical industry as well as any other companies with an explosion protected area.

Due to the short preparation time and easy handling are the units quick serviceable to recover dust or solid product rests.

The units are designed with a detachable recovery tank on wheels with a capacity of 35 or 50 liters. The goods can be recovered directly in the stainless steel tank or in a conductive polyliner bag with a special lid. The bags are very useable for easy emptying of recovered materials and for the dust-free disposal.

The vacuum cleaner will be delivered with a M (1 micron) filter and a HEPA filter (Type H14, efficiency of 99.999%). The filter can be cleaned with the filter cleaning systems FDR (manual reverse purge).

Part number

see accessories catalogue

see accessories catalogue

see accessories catalogue

Features / Advantages

- Can be used to recover flammable dust
- Mobile units

Accessories Type

Polyliner bag Suction hose EX

Nozzles EX

Separator EX

- Filter cleaning system FDR
- Easy handling and virtually maintenance free
- · Highest safety and technical quality
- All stainless steel construction incl. cart
- Reduced noise level
- Robust yet light weight
- Filter units can be cleaned and changed very easy

2003452





FDR Filter cleaning system





Polyliner bag with lid

Manometer



	١I	accessories	are	made	of	electrical	conductive	materials.
--	----	-------------	-----	------	----	------------	------------	------------

Technical features	Туре	Liter	Filterclass	Medium	Part no.			
Drive	Pneumatically air operated	DGS 35 EX	35	M/H	flammable dust	2004982		
Input air volume	34m³/h	DGS 50 EX	50	M/H	flammable dust	2004984		
Input air pressure min. 4,5 bar								
Suction volume	145 m³/h max.							
Vacuum	240 mbar max.							
Capacity	35 / 50 Liter							
Filter area	20.000 cm ²							
Hose entry60mm (can be reduced)Weight35 / 36,5 kgNoise level72 dB (A)Dimensions LxWxH700x600x1240 / 1390 mm		Supplied with:	Part no.					
		Filter 1: Prefilte	2009550					
		Filter 2: Mainfilt	2003996					
Also available with dou	FDR Filter clea	ning system	1		2005010			