

high grade + large filter + pharma

**Industrial vacuum for dust**

Electric

**EP 2115**

**EP 2122-35**

**Mobile high-performance industrial vacuum cleaner for dry products**

**Range of application**

High performance industrial vacuum cleaner designed for sucking up dust. The rugged construction suitable for rugged industrial use. Can also be used in small tube or systems with long suction hoses.

**Properties/Advantages**

- Continuous Fixed side channel blowers
- Highest technical security
- Very robust
- Soundproofed turbo fan
- Effective, easy-to-use filter for long filter life
- Vacuum gauge for filter monitoring
- Simple operation and maintenance



Also available in B1 /  Zone 22

The standard model sucks on a tangential inlet the suction material into the hopper. For a safe attachment of the suction hose ensures a quick release with locking device and rotating device.

The mechanical filter allows the user an effective cleaning of the filter stage 1 The extremely simple operation and cleaning capabilities of the vacuum cleaner designed specifically for industrial applications.

The industrial vacuum cleaners are the BGIA (BG Institute for Occupational Safety) "GS" approved. Depending on the application, we provide safety-tested in dust class M with a max. Transmittance of dust at <0.1% (dry, health-hazardous, non-combustible dusts with MAK values > 0.1 mg / m³), dust class H with a max. Transmittance of <0.005% (dry, carcinogenic, non-combustible dusts with MAK-value <0.1 mg / m³).

The industrial vacuum cleaners are also available in version B1 and ATEX (Ex-zone 22) or in dust class M/B1 M/H/B1. Thus, the industrial vacuum cleaner suitable (except dusts with a minimum ignition energy <1mJ) to absorb all the dust from combustible dust explosion classes.



Removable tank



Tension rings



H-Filter



Vacuum relieve valve

Accessories		Modell	Cont./L	Dust class	Art.Nr.
<b>Description</b>	<b>Art.Nr.</b>	EP 2115	35	M	2012431
Suction hose	see catalogue	EP 2115	35	M / B1	2012434
Suction accessories	see catalogue	EP 2115	35	H	2012432
		EP 2115	35	H / B1	2012433
<b>Technical data</b>		EP 2122-35	35	M	2009937
Engine	electric motor	EP 2122-35	35	M / B1	2009935
Power	1,5 / 2,2 kW	EP 2122-35	35	H	2009938
Engine performance	400 V / IP55	EP 2122-35	35	H / B1	2009936
Intake volume max.	200 / 351 m³/h, max.				
Vacuum max.	2050 / 240 mbar, max.				
Tank	35 l				
Filter area	1,75 m²				
Hose connecting	80 mm, reduceable				
Weight	105 kg				
Dimensions l / w / h	1190x580x1220 mm				
		<b>Scope of delivery</b>		<b>Art.Nr.</b>	
		after technical clarification			